



FEATURES:

- Used for kitting and to help organize the workstation
- Durable conductive styrene
- Die-cut drop-in covers available separately
- Reusable, ensuring best value
- Great container for Kanban
- Made in America

SPECIFICATIONS:

Property	Typical Value	ASTM
Specific Gravity	1.09	D-792
Tensile Strength	4,200 psi	D-638
Tensile Elongation	40%	D-638
Flexural Modulus	220,000 psi	D-790
Flexural Strength	6,700 psi	D-790
Total/Free Sulfur	<0.15% / <0.004%	
Chlorides	<0.3 PPM	
Outgassing & Corrosivity	Low	
5KV Decay Time	<0.01 sec @ 10% RH	
Surface Resistance	10 ⁴ Ohms	

Item	Size (inches)	Cell Size (inches)	# of Cells
39206	10-1/2 x 8-3/4 x 1-1/2	2 x 1-7/8 x 1	12
39201	14-1/2 x 10-1/8 x 1-7/8	3-1/2 x 2-3/4 x 1-1/4	9
39202	14-3/8 x 10-1/8 x 1-3/4	3 x 3 x 1-1/4	12
39203	Lid for Kitting Tray 39206		
39204	Lid for Kitting Tray 39201		
39205	Lid for Kitting Tray 39202		

CONDUCTIVE KITTING TRAYS

PROTEKTIVE PAK

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
ProtektivePak.com

DRAWING NUMBER
39201

DATE:
September
2009